


Cat5e Ethernet Bulk Cable

24AWG • 4 Twisted Pairs • CMR • F/UTP • 350MHz • Solid Copper



Overview

Cat5e cable is a "twisted pair" network cable used for 1000Base-T Ethernet applications at speed of up to 350MHz of bandwidth. This cable is preferred for more advanced networking installations where a higher bandwidth than normal is required.



Key Features

- Solid Bare Copper Better than CCA
- Tangle and Twist-free Packaging
- Marked Every 1m (3.28ft) on Cable Makes Measuring Easy
- Support PoE, PoE+ (IEEE 802.3af/at)
- CE, Reach, RoHS Certified
- Shielding Helps Eliminate Cross-talk and Prevents Electromagnetic Interference (EMI)
- CMR Rated (Riser) for Use in between Floors, in-Wall, and Non-plenum Spaces
- Tested with a Fluke DSX-8000 Versiv CableAnalyzer

Application

- Use in between Floors, In-Wall, and Non-plenum Spaces
- Rated for any 10/100/1000Base-T Ethernet
- Connect with Switches, Routers, Computers, IP Cameras, Xbox, Apple TV and Much More

Specifications

Physical Characteristics

Operating Temp. Range	-20 to +75°C (-4 to 167°F)
Max. Operating Voltage (v)	80
Reference Standard	ISO/IEC 11801, ANSI/TIA-568.2-D

Conductor

Material	Solid Bare Copper
Wire Gauge (AWG)	24
Conductor Nom.O.D. (mm)	0.500 ± 0.005
Conductor Qty.	4 Twisted Pairs

Insulation

Insulation Material	HDPE
Insulation Diameter (mm)	1.00 ± 0.05
Core Color	A. White - Blue, Blue B. White - Orange, Orange C. White - Green, Green D. White - Brown, Brown

Jacket

Material	PVC (Complies RoHS), CMR
External O.D. (mm)	6.2 ± 0.4
Thickness (mm)	0.55 ± 0.05
Color	Blue
Surface	Clean, Frap, Satiation
Rip Cord	Yes

Specifications

Electrical Characteristics

1.0-100.0MHz Impedance (ohms)	100 ± 15
1.0-100.0MHz Delay Skew (ns/100m)	≤45
Capacitance Unbalance (pF/100m)	≤160
Max. Conductor DC Resistance @20°C (ohms/100m)	9.5
Resistance Unbalance (%)	≤5.0

Mechanical Characteristics

Before Aging Tensile Strength (Mpa)	≥13.5
Before Aging Elongation (%)	≥150
Aging Period (°C×hrs)	100°C×24h×7d
After Aging Tensile Strength (Mpa)	≥12.5
After Aging Elongation (%)	≥125
Cold Bend (-20±2°C×4h)	8 × Cable O.D., No Visible Cracks

Packing

Packing Type	1000ft (305m)/Spool
--------------	---------------------



 <https://www.fs.com>



The information in this document is subject to change without notice. FS has made all efforts to ensure the accuracy of the information, but all information in this document does not constitute any kind of warranty.